

常用公差标准对比

KERLO



凯尔洛

第一等级

标准		GBT3672.1-2002等同于ISO 3302-1-1996E		GBT1804-2000等同于 ISO2768-1-1989		RMA	
标准尺寸		M1		f		A1	
以上 >	以下(包含) ≤	F	C	±	±	F	C
		±	±			±	±
0	0.5	0.08	0.1		需给出	0.1	0.13
0.5	3	0.08	0.1		0.05	0.1	0.13
3	4	0.08	0.1		0.05	0.1	0.13
4	6	0.1	0.12		0.05	0.1	0.13
6	6.3	0.1	0.12		0.1	0.1	0.13
6.3	10	0.1	0.15		0.1	0.1	0.13
10	16	0.15	0.2		0.1	0.13	0.16
16	25	0.2	0.2		0.1	0.16	0.2
25	30	0.2	0.25		0.1	0.2	0.25
30	40	0.2	0.25		0.15	0.2	0.25
40	63	0.25	0.25		0.15	0.25	0.32
63	100	0.35	0.4		0.15	0.32	0.4
100	120	0.4	0.5		0.15	0.4	0.5
120	160	0.4	0.5		0.2	0.4	0.5
160	400	0.30%	0.40%		0.2	-	-
400	1000	0.30%	0.40%		0.3	-	-
1000	2000	0.30%	0.40%		0.5	-	-
2000	4000	0.30%	0.40%		-	-	-
4000	over	0.30%	0.40%		-	-	-

第二等级

标准		GBT3672.1-2002等同于ISO 3302-1-1996E		GBT1804-2000等同于 ISO2768-1-1989		RMA	
标准尺寸		M2		m		A2	
以上 >	以下(包含) ≤	F	C	±	±	F	C
		±	±			±	±
0	0.5	0.1	0.15		需给出	0.16	0.2
0.5	3	0.1	0.15		0.1	0.16	0.2
3	4	0.1	0.15		0.1	0.16	0.2
4	6	0.15	0.2		0.1	0.16	0.2
6	6.3	0.15	0.2		0.2	0.16	0.2
6.3	10	0.2	0.2		0.2	0.16	0.2
10	16	0.2	0.25		0.2	0.2	0.25
16	25	0.25	0.35		0.2	0.25	0.32
25	30	0.35	0.4		0.2	0.32	0.4
30	40	0.35	0.4		0.3	0.32	0.4
40	63	0.4	0.5		0.3	0.4	0.5
63	100	0.5	0.7		0.3	0.5	0.63
100	120	0.7	0.8		0.3	0.63	0.8
120	160	0.7	0.8		0.5	0.63	0.8
160	400	0.50%	0.80%		0.5	0.40%	0.50%
400	1000	0.50%	0.80%		0.8	0.40%	0.50%
1000	2000	0.50%	0.80%		1.2	0.40%	0.50%
2000	4000	0.50%	0.80%		2	0.40%	0.50%
4000	over	0.50%	0.80%		-	0.40%	0.50%

常用公差标准对比



第三等级

标准		GBT3672.1-2002等同于ISO 3302-1-1996E		GBT1804-2000等同于 ISO2768-1-1989		RMA	
标准尺寸		M3		C		A3	
以上 >	以下(包含) ≤	F	C	±	F	C	
		±	±		±	±	
0	0.5	0.25	0.4	需给出	0.2	0.32	
0.5	3	0.25	0.4	0.2	0.2	0.32	
3	4	0.25	0.4	0.3	0.2	0.32	
4	6	0.25	0.4	0.3	0.2	0.32	
6	6.3	0.25	0.4	0.5	0.2	0.32	
6.3	10	0.3	0.5	0.5	0.2	0.32	
10	16	0.4	0.6	0.5	0.25	0.4	
16	25	0.5	0.8	0.5	0.32	0.5	
25	30	0.6	1	0.5	0.4	0.63	
30	40	0.6	1	0.8	0.4	0.63	
40	63	0.8	1.3	0.8	0.5	0.8	
63	100	1	1.6	0.8	0.63	1	
100	120	1.3	2	0.8	0.8	1.25	
120	160	1.3	2	1.2	0.8	1.25	
160	400	0.80%	1.30%	1.2	0.50%	0.80%	
400	1000	0.80%	1.30%	2	0.50%	0.80%	
1000	2000	0.80%	1.30%	3	0.50%	0.80%	
2000	4000	0.80%	1.30%	4	0.50%	0.80%	
4000	over	0.80%	1.30%	-	0.50%	0.80%	

第四等级

标准		GBT3672.1-2002等同于ISO 3302-1-1996E		GBT1804-2000等同于 ISO2768-1-1989		RMA	
标准尺寸		M4		v		A4	
以上 >	以下(包含) ≤	F	C	±	F	C	
		±	±		±	±	
0	0.5	0.5	0.5	需给出	0.32	0.8	
0.5	3	0.5	0.5	-	0.32	0.8	
3	4	0.5	0.5	0.5	0.32	0.8	
4	6	0.5	0.5	0.5	0.32	0.8	
6	6.3	0.5	0.5	1	0.32	0.8	
6.3	10	0.7	0.7	1	0.32	0.8	
10	16	0.8	0.8	1	0.4	0.9	
16	25	1	1	1	0.5	1	
25	30	1.3	1.3	1	0.63	1.12	
30	40	1.3	1.3	1.5	0.63	1.12	
40	63	1.6	1.6	1.5	0.8	1.25	
63	100	2	2	1.5	1	1.4	
100	120	2.5	2.5	1.5	1.25	1.6	
120	160	2.5	2.5	2.5	1.25	1.6	
160	400	1.50%	2.5	2.5	0.80%	1.00%	
400	1000	1.50%	4	4	0.80%	1.00%	
1000	2000	1.50%	6	6	0.80%	1.00%	
2000	4000	1.50%	8	8	0.80%	1.00%	
4000	over	1.50%	-	-	0.80%	1.00%	